

# DIMIC1

All call digital paging station for AUDIOCONTROL12.8



DIMIC1 is an all call digital paging station for use with AUDIOCONTROL12.8 that is easy to configure via the host's graphical installer interface.

In most applications an all call microphone is indispensable to guarantee a good communication. Apart's DIMIC1 microphone is especially designed to function in a plug and play way with our electronics and makes sure that your message will be heard loud and clear throughout the entire office.

DIMIC1 combines an inconspicuous and elegant design with a remarkable sound quality. It has speech-optimized sound processing and a unidirectional condenser microphone.

The unit has Universal configuration of push buttons, an all zone selection button and a push-to-talk button and multicolor paging status LED's.

## TECHNICAL SPECIFICATIONS

<b>width in mm</b>	110	<b>depth in mm</b>	240
<b>height in mm</b>	58	<b>weight in gr</b>	600
<b>cut-out dimension in mm</b>	85 x 230	<b>active</b>	Yes
<b>polar pattern</b>	uni-directional	<b>buttons</b>	all zone selection button
<b>indicator</b>	tri-color status	<b>nominal output level</b>	775mV variable balanced
<b>frequency range</b>	220 Hz - 20 kHz	<b>lo-cut</b>	220 Hz, 6dB/oct
<b>power type</b>	Phantom or external power supply	<b>external power supply</b>	12 - 24Vdc/75mA
<b>mic stem length in mm</b>	395	<b>cable length in m</b>	5
<b>connector</b>	RJ45	<b>cable type</b>	CAT5
<b>supported main unit</b>	AUDIOCONTROL12.8	<b>Net weight product (kg)</b>	0,60

[MORE PICTURES](#)



## ACCESSORIES



### **RJ45SPLIT**

RJ45 Splitter : 1input, 4 output (MICPAT-4 or ZONE4R)